



LLC

PO Box 39
Peapack, NJ 07977
866-631-4423
815-377-4001 (fax)

Material Safety Data Sheet

Naf's OMG! Premium Base Coat (Paint Enhancer)

Effective 8/15/2007

Section 1 – Chemical Product and Company

C.I. Name: White pigment Dispersion Blend
C.I. Number: N/A
Product Use: Whitening agent
Synonyms: OMG! Premium Base Coat Paint Enhancer – 1TP-107

Section 2 – Hazardous Ingredients

This product contains no hazardous Pigments, Vehicles or Solvents

Section 3 – Physical Data

Boiling Point:	212°F	Specific Gravity:	1.92
Vapor Pressure		Percent, Volatile	
Vapor Density	Heavier than Air	By Volume	67%
Solubility in Water	100%	Evaporation Rate	Slower than Ether
Appearance and Odor	White and Mild	Wgt per Gallon (lbs)	16.0 +/- 0.2

Section 4 – Fire and Explosion Hazard Data

Flash Point:

200°F +

Flammable Limits:

Level 5.5

Extinguishing Media:

Dry Chemical

Special Fire Fighting Procedures:

Keep materials from heat, spark, and open flame

Unusual Fire and Explosion Hazards

Water should be used to cool containers

Section 5 – Health Hazard Data

Emergency and First Aid Procedures

First Aid: Inhalation

Remove person to fresh air

First Aid: Skin Contact

Wash with soap and water

Eye Contact:

Flush eyes with water for at least 15 minutes. Contact Physician

Section 6 – Reactivity Data

Stability:

This product is stable

Conditions to avoid:

None known

Hazardous Polymerization:

Will Not occur

Incompatibility (Materials to avoid):

None known

Section 7 – Spill or Leak Procedures

Steps To Be Taken In Case Of Material Released Or Spilled:

Remove all sources of ignition and ventilate vapors. Absorb with an inert material

Waste Disposal Method:

Dispose in accordance with Federal, State, and Local regulation.

Section 8 Special Protection Information

Note: Selecting protective equipment & clothing:

When choosing personal protective equipment and clothing, consider each worker environment, all chemicals being handled, temperature and all other conditions.

Respiratory Protection:

Adequate ventilation is required. Use a respirator in confined areas as approved by US Bureau of Mines.

Ventilation:

Provide sufficient ventilation to keep vapor concentrations below T.V and L.E.L.

Eye Protection:

Use eye protection sufficient to prevent eye contact

Skin Protection:

Gloves are required for prolonged contact with product

Eye Washes and Other Protection:

Eye wash stations and drench showers should be located within 100 feet or a 10-second walk of the work area per ANSI standard Z358.1-1990.

*****Section 9 – Special Precautions*****

Close containers after each use.
Avoid damage to containers to prevent spills.
Keep material from heat, sparks, and open flames.

*****Section 10 – Other Information*****

Disclaimer

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind expressed or implied, is made with respect to the information contained herein. This Material Safety Data Sheet was prepared to comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200, and supersedes any previous information.

END OF MSDS